



CERTIFICATE OF PRODUCT CERTIFICATION

SOLAR PRODUCT CERTIFICATE

CERTIFICATE NO.: CQC24024445489

Valid from: Sep.14,2024

Valid until:Aug.19,2029

NAME AND REGISTERED ADDRESS OF THE APPLICANT	Shenzhen Skyworth Photovol-taic Technology Co., Ltd. 0801, Block C, Building 5, Huaqiang Creative Park, Biyan Community, Guangming Street, Guangming District, Shenzhen
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	Shenzhen Skyworth Photovol-taic Technology Co., Ltd. 0801, Block C, Building 5, Huaqiang Creative Park, Biyan Community, Guangming Street, Guangming District, Shenzhen
NAME AND LOCATION OF THE FACTORY	JIANGSU SKYWORTH NEW ENERGY TECHNOLOGY CO., LTD South 3rd floor, No.4 Factory, No.599 Taishan Road, Suzhou High-tech Zone
PRODUCT NAME, MODEL AND SPECIFICATION	PV GRID-CONNECTED INVERTER CWH033TN-200222L、CWH030TN-200222L、CWH030TN-200212L (see appendix)
THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS	NB/T32004-2018(without weighted efficiency test and fault ride through test)
TYPE OF CERTIFICATION SCHEMES	Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC33-461239-2018.
The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE OF PRODUCT CERTIFICATION

SOLAR PRODUCT CERTIFICATE

APPENDIX

Page 1 of 1

CERTIFICATE NO.: CQC24024445489

PAPER:

CWH033TN-200222L

直流输入:MPPT 电压范围 160V-1000Vdc, 最大直流输入电压 1100Vdc, 最大输入电流 3*40 A; 交流输出: 3/N/PE, 230/400V, 50Hz, Max. 52.6A, 额定交流输出功率 33kW。

CWH030TN-200222L

直流输入:MPPT 电压范围 160V-1000Vdc, 最大直流输入电压 1100Vdc, 最大输入电流 3*40 A; 交流输出: 3/N/PE, 230/400V, 50Hz, Max. 47.8A, 额定交流输出功率 30kW。

CWH030TN-200212L

直流输入:MPPT 电压范围 160V-1000Vdc, 最大直流输入电压 1100Vdc, 最大输入电流 40/20/40A; 交流输出: 3/N/PE, 230/400V, 50Hz, Max. 47.8A, 额定交流输出功率 30kW。

NOTE: This appendix is valid when used with the certificate.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE